



CLEVERTRONICS LP PREMIUM SUSTAINED LED TUBE EMERGENCY BATTEN & LED POD



PRODUCT INFORMATION

| | |
|-----------------------|---|
| Catalogue Number | CBS1L2S-DIF |
| Description | Wide Body Diffused Batten with LED Tubes |
| Construction | Powder Coated Steel |
| Mounting | Surface Mount |
| Dimensions L x W x H | 666mm x 120mm x 110mm |
| Operating Mode | Sustained/Combined Non-Maintained. On/off control of the LED tube via switched active input. Non-Maintained LED emergency function. |
| Testing System | Manual Test Switch |
| Diffuser | Prismatic |
| LED Tube(s) | 1 x 600mm LED Tube 840 G13 880lm 50,000 Hours |
| Operating Voltage | 240V, 50Hz |
| Charging Method | Intelligent current limited constant voltage charger |
| Emergency Lamp Source | 2 x 3W LED (Lifetime warranty on the lamp head and loom assembly) No dome cover required |
| IP Rating | IP20 |
| Operating Temperature | 10° to 40°C |
| Power Consumption | 9W (Lamps On) 1W (Lamps Off) |
| AS2293 Classification | C ₀ = D40 C ₉₀ = D40 |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|---|
| 3170025 | Lamp, LED Tube 8W 4000K |
| 1100640 | Lamp, Lifelight Pro Head and Heatsink |
| 1120320 | Lamp Holder T8 |
| 2300060 | Diffuser 14/18W Wide |
| 2900012 | Shanghai End Cap |
| 1550050 | Battery, LP 3.2V 3200 mAh 70mm Lead, No Bracket |
| 8002530 | PCA, LP Lifelight Driver ZWC, CT#10260-L3 |