

LED BOXLITE™ EXIT



2.9W POWER CONSUMPTION - Energy efficient.

EASY INSTALL - Quick connect bracket for fast ceiling or wall mounting. Large terminal block & cable entry hole for easy installation.

EASY MAINTENANCE - All diffuser options in one box.

LONG LIFE LED - Energy efficient, Long life. Available in economy 50,000hr LED.

For over 20 years, the Clevertronics Boxlite has provided a quality solution to Contractors requiring a conventional style exit for easy retrofitting, now available with the advantage of long lasting LED.

Boxlite uses a universal body that can be supplied with diffuser combinations for Wall and Ceiling mounting. The body uses a detachable base plate that can be mounted and wired into position first. The gear tray can then be plugged in and secured when installation is completed.

All diffuser combinations for single-sided or double-sided, 'EXIT' or 'Pictograph' options, can be configured on site from the one box.

ONE BOX SOLUTION - ALL OPTIONS

AS2293 requirements have never been easier to meet with all diffuser options in one box.

PICK



Pick the correct decal

SLIP



Slip it in

CLIP



Clip it shut

As of 2005 the Australian Standard for emergency lighting requires all new applications and major refurbishments to have the 'pictograph' legend on an exit. It is still best practice to match 'EXIT' for 'EXIT' in a building built prior to this change.

LED BOXLITE™ EXIT

SEGMENT - LAMP TYPE	PART NUMBER & MOUNTING OPTIONS	
	Single-point	Mounting
ECONOMY - LED	EBLLED-WM	WALL
ECONOMY - LED	EBLLED-CM	CEILING


ECONOMY LED

Surface mounted wall or ceiling box style exit, long life Maintained LED technology, pulse charge high temperature Nickel Cadmium battery, 1 year back to base warranty, single and double sided and directional options configurable on site. Available as wall or ceiling mounted exit with opal diffuser.

SPECIFICATIONS				
	Warranty	Power Consumption	C0	C90
EBLLED-WM	1 YEAR	2.9W	E1.6	E2
EBLLED-CM	1 YEAR	2.9W	D5	D5



Dimensions (mm)
Wall Mount




Dimensions (mm)
Ceiling Mount

SPACING TABLE & MOUNTING HEIGHTS											
Classification	2.1m	2.4m	2.7m	3m	3.3m	3.6m	4m	4.5m	5m	6m	7m
E1.6	4.8	4.8	4.8	4.4	4.0	4.2	3.8	-	-	-	-
E2	5.2	5.2	5.4	5.2	5.0	4.6	4.8	-	-	-	-
D5	7.8	8.0	8.1	8.2	8.2	8.2	8.0	7.7	7.3	5.7	1.6

Based on minimum light level of 0.2 lux

Maximum allowed mounting height is 2.7m but for exceptions see AS/NZS2293.1 2005

SPARE PARTS					
	Battery	Lamp	Clevertest™ Node	Zoneworks® Node	Diffuser
EBLLED-WM	1510325	8002290	N/A	N/A	EBLD-WM
EBLLED-CM	1510325	8002290	N/A	N/A	EBLD-CM



Ceiling Mount Wire Guard
Part number: 2530110
Dimensions (mm) L x W x H
407 x 267 x 190



Wall Mount Wire Guard
Part number: 2530050
Dimensions (mm) L x W x H
439 x 120 x 225

Version: October 2014-4

Please check our website for your closest Clevertronics office and local representative. Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.

www.clevertronics.com.au