



CLEVERTRONICS ECONOMY LED TUBE DIFFUSED BATTEN



PRODUCT INFORMATION

Catalogue Number	EBS2L4S-DIF
Description	Economy LED tube diffused batten with LED emergency POD
Construction	Powder coated steel and ABS/Polycarbonate end caps
Mounting	Surface mount
Dimensions L x W x H	1274mm x 120mm x 110mm
Operating Mode	Sustained
Testing System	N/A - Manual test switch
Charging Method	Constant Current (16hrs); Pulse Charge (Standby)
Diffuser	Prismatic
Lamp(s)	2x Philips Essential LEDtube T8, Col. 840, 2820lm, 30,000hours
Operating Voltage	250V AC; 50Hz
Power Consumption	36 Watts (lamp ON), 0.7 Watts (Standby)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1510425	4SubC NiCad Batt. Pk 4.8V 1.5Ah,SBS,Bkt.
8002580	PCA:ELIFE Batten Adaptor Head
ELIFE-X-CKIT-NP	Lifelight, Control Only, Eco, No Plug
3170080	ESSENTIAL LED TUBE 18W/840, 1.2m

ECONOMY
NiCd BATTERY RANGE