

CLEVERTRONICS TEMPORARY LIGHTING DUAL 24V DC WEATHERPROOF POWER SUPPLY



PRODUCT INFORMATION

Part Number	TW2PS24V24A
Description	<p>Temporary Lighting Weatherproof Dual Output 24V DC Power Supply, 24A IP65. Supplied with 2 short length flex and plug outputs for connection to the temporary lighting cabling system.</p> <p>The TW2PS24V24A is also supplied with a Dual 24V DC output switch that allows the general lighting supply to be switched off at the TW2PS24V24A whilst still maintaining a permanent supply to continuously charge the battery.</p>
Construction	Metal enclosure
Mounting	Surface mount
Dimensions L x W x H	400mm x 400mm x 200mm
Weight	14.5kg
Charging Method	Intelligent current limited constant voltage
Operating Voltage	240V AC; 50Hz
Rated Output Voltage	24V DC (SELV)
Rated Output Current	24A (Combined, nominal output of the two power supplies). Absolute maximum rated current for each power supply at 24V is 13.34A)
IP Rating	IP66
Impact Rating	IK10
Operating Temperature	0°C to 40°C

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1196701	Power Supply, Mean Well HLG-320H-24A (2)

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order