



TEMP-48V-1200-EM

Temporary Lighting 48V 1200mm Weatherproof Emergency Batten, End to End Flex and Plug



PRODUCT INFORMATION

Part Number	TEMP-48V-1200-EM
MIC	AUB00000009801
Description	Temporary Lighting 48V 1200mm Weatherproof Emergency Batten, End to End Flex and Plug
Construction	Polycarbonate case kit and diffuser
Mounting	Chain suspension or surface mount (brackets pre-installed, no need to open luminaire)
Dimensions L x W x H	1264mm x 88mm x 81mm
Weight (kg)	1.7
Operating Mode	Sustained
Testing System	N/A – Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 3000mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Polycarbonate
Driver / Ballast	48V constant current driver
Lamp(s)	LED strip module L70/B50 Ta 40°C; Reported > 72,000h, projected > 152,250h
Colour Temperature	4000K natural white
Colour Rendering Index (CRI)	Ra ≥ 80
Operating Voltage	38-54V DC
Total lumen output	3626lm @150lm/W
Power Consumption	24.1W (standby charge, main lamp on), 26.2W (max charge, main lamp on)
IP Rating	IP65
Impact Rating	IK08
Operating Temperature	0°C to 40°C
AS/NZS 2293.3, AS/NZS 3012 Classification*	C0=D80/C200, C90=D50/C200, C180=D80/C200, C270=D50/C200
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS60598-2.22, AS/NZS2293.3 (with AS/NZS 3012 deviation)
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560150	BATT:LiFePO4 3.2V 3.0Ah 70mm lead,noBRKT
271-00006	Temporary Lighting 48V 1200mm IP65 batten diffuser

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.