



TEMP-48V-1200

Temporary Lighting 48V 1200mm Weatherproof Batten, End to End Flex and Plug



PRODUCT INFORMATION

Part Number	TEMP-48V-1200
MIC	AUB00000011201
Description	Temporary Lighting 48V 1200mm Weatherproof Batten, End to End Flex and Plug
Construction	Polycarbonate case kit and diffuser
Mounting	Chain suspension or surface mount (brackets pre-installed, no need to open luminaire)
Dimensions L x W x H	1264mm x 88mm x 81mm
Weight (kg)	1.6
Diffuser	Polycarbonate
Driver / Ballast	48V constant current driver
Lamp(s)	LED strip module L70/B50 Ta 40°C; Reported > 72,000h, projected > 152,250h
Colour Temperature	4000K natural white
Colour Rendering Index (CRI)	Ra ≥ 80
Operating Voltage	38-54V DC
Total lumen output	3626lm @150lm/W
Power Consumption	24W
IP Rating	IP65
Impact Rating	IK08
Operating Temperature	0°C to 40°C
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS60598.2.1
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
271-00006	Temporary Lighting 48V 1200mm IP65 batten diffuser

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.