



TEMP-48V-PS

Temporary Lighting 48V Dual Output Weatherproof Power Supply



PRODUCT INFORMATION

Part Number	TEMP-48V-PS
MIC	AUL00000000301
Description	Temporary Lighting 48V Dual Output Weatherproof Power Supply. Supplied with 2 short flex and plug outputs for connection to the temporary lighting cabling system. The TEMP-48V-PS also includes a DC output switch that allows the general lighting supply to be switched off at the unit whilst still maintaining a permanent supply to continuously charge the battery.
Construction	Metal enclosure
Mounting	Surface mount
Dimensions L x W x H	400mmx 400mm x 200mm
Weight (kg)	20
Charging Method	Intelligent current limited constant voltage
Operating Voltage	240V AC; 50Hz
Rated Output Voltage	48V DC (SELV)
Rated Output Current	20A (Combined, nominal output of the two lines. Absolute maximum rated current for each line at 48V is 12.5A)
Number of Connected Fittings	Up to 15 emergency battens per line, or 30 emergency battens per power supply (double line) with 8m interconnection cables.
IP Rating	IP66
Impact Rating	IK10
Operating Temperature	0°C to 40°C
Applicable Standards	IEC 61558-2-16, IEC 61558-1, AS/NZS 61558.2.16, AS/NZS 61558.1
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
133-00009	Power Supply Mean Well HLG-600H-48A

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.