



TEMP-48V-WFLED

Temporary Lighting 48V Weatherproof 4 Head Flood Light, Non-emergency, End to End Flex and Plug



PRODUCT INFORMATION

Part Number	TEMP-48V-WFLED
MIC	AUT00000009201
Description	Temporary Lighting 48V Weatherproof 4 Head Flood Light, Non-Emergency, End to End Flex and Plug
Construction	Polycarbonate enclosure and aluminium flood light head
Mounting	Surface mount
Dimensions L x W x H	Total: 395mm x 100mm x 300mm Enclosure: 150mm x 100mm x 250mm
Weight (kg)	2.35
Driver / Ballast	48V constant current driver
Lamp(s)	4 x adjustable LED heads L70/B50 Ta 40°C; Reported > 60,000h, projected > 148,790h
Colour Temperature	4000K natural white
Colour Rendering Index (CRI)	Ra ≥ 80
Operating Voltage	38-54V DC
Total lumen output	3327lm, 831.75lm per head
Power Consumption	36W
IP Rating	IP65
Impact Rating	IK08
Operating Temperature	0°C to 40°C
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS60598.2.1
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1100550	WP LED Head, c/w LED's & Loom, Gland (x4)

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.