



TEMP-48V-CFLED

Temporary Lighting 48V Cleverfit Exit with Flex and Plug



PRODUCT INFORMATION	
Part Number	TEMP-48V-CFLED
MIC	AUA00000018601
Description	Temporary Lighting 48V Cleverfit Exit with Flex and Plug
Construction	ABS Body and Diffuser with Polycarbonate Clear Decal Cover and 1m Flex and Plug
Mounting	Wall Mount Single-sided or Chain Suspension
Dimensions L x W x H	355mm x 215mm x 80mm
Weight	1.2kg
Operating Mode	Maintained
Testing System	N/A – Manual Test Switch
Battery	Lithium Iron Phosphate, 3.2V 600mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All Directional Inserts Included in the Box
Lamp(s)	4 x LED Lamp Bar Assembly, Lifetime: >50,000hrs
Operating Voltage	38-52V DC
Power Consumption	1.5 Watts (Standby), 2.7 Watts (Max)
IP Rating	IP20
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D4 C90=E2.5
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	<input type="checkbox"/> Class II double insulated, noiseless (clean) earth (ground) terminal (not a protective earth and used for EMC purposes only)

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550195	Battery

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.