



## TEMP-48V-PS-ELTK

Temporary Lighting 48V Dual Output Weatherproof Power Supply with Manual Test Switch



### PRODUCT INFORMATION

Part Number	TEMP-48V-PS-ELTK
MIC	AUL00000000401
Description	<p>Temporary Lighting 48V Dual Output Weatherproof Power Supply With Manual Test Switch.</p> <p>Supplied With 2 Short Flex and Plug Outputs for Connection to the Temporary Lighting Cabling System.</p> <p>The TEMP-48V-PS-ELTK also Includes an Integrated Emergency Lighting Test Timer and a DC Output Switch That Allows the General Lighting Supply to Be Switched Off at the Unit Whilst Still Maintaining a Permanent Supply to Continuously Charge the Battery.</p>
Timer Configuration	Set to 90 Min Discharge Test Time with Automatic Reset (Can Be Set to a Maximum of 10 Hours)
Construction	Metal Enclosure
Mounting	Surface Mount
Dimensions L x W x H	400mmx 400mm x 200mm
Weight	20kg
Operating Voltage	240V AC; 50Hz
Rated Output Voltage	48V DC (SELV)
Rated Output Current	20A
Number of Connected Fittings	Up to 30 Emergency Batters Per Power Supply (Double Line) or 15 Emergency Batters Per Line With 8m Interconnection Cables.
IP Rating	IP66
Impact Rating	IK10
Operating Temperature	0°C to 40°C
Applicable Standards	IEC 61558-2-16, IEC 61558-1, AS/NZS 61558.2.16, AS/NZS 61558.1
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
133-00014	Power Supply Mean Well XDR-960E-48

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.