



## CLEVERTRONICS LP DIFFUSED PRO BATTEN



### PRODUCT INFORMATION

Catalogue Number	CBS118S-DIF-A2
Description	1 x 18 Watt LP Premium, PRO diffused batten with LP LED emergency POD
Construction	Powder coated steel body, Acrylic prismatic diffuser and ABS/Polycarbonate end caps
Mounting	Surface mount
Dimensions L x W x H	666mm x 120mm x 110mm
Operating Mode	Sustained
Testing System	N/A - Manual test switch
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Prismatic
Ballast	Electronic
Lamp(s)	T8 Cool White Tri-Phosphorous 18W/840
Operating Voltage	240V AC; 50Hz
Power Consumption	19 Watts (lamps ON), 1.0 Watts (lamps OFF)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D40 C <sub>90</sub> =D40

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery, LP 3.2V 3200mAh 70mm lead, no Bracket
3100175	18w/840, Coolwhite Lamp
1120212	Lampholder 28/35w T8>T5 Adapt, T/S1120215
8002530	PCA:LP Lifelight Driver ZWC, #CT10260-L3