



## CLEVERTRONICS LP PREMIUM DIFFUSED BATTEN WITH INTEGRATED LED EMERGENCY



### PRODUCT INFORMATION

Catalogue Number	CBS118S-DIF
Description	1 X 18 Watt LP Diffused Batten With Premium Lithium LED Emergency
Construction	Powder Coated Steel body and Polycarbonate Lamp Holders
Mounting	Surface Mount
Dimensions L x W x H	666mm x 120mm x 110mm
Operating Mode	Sustained
Testing System	Manual Test Switch
Charging Method	Intelligent current limited constant voltage charger
Ballast	Electronic , 1x18W, EEI=A3
Lamp(s)	T8 Cool white Tri-Phosphor 18W/840
Operating Voltage	240V
Power Consumption	19W (Lamps ON) 1.0W Standby
IP Rating	IP20
Operating Temperature	10° to 40°C
AS/NZ2293 Classification	C <sub>0</sub> =D40 C <sub>90</sub> =C40

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1310103	Ballast, VS FBC118 Electronic, 1 x 18W, EEI=A3
3100175	Lamp(s) T8 18W/840 COOLWHITE TUBE
1120320	Lamp Holder T8
2300060	Diffuser 14/18W wide
2750064	LP Batten Emergency End Cap (includes LED Assembly and Battery)
1550050	Battery, LP 3.2V 3200mAh 70mm lead,no BRKT.
8002530	PCA: LP Lifelight Driver, Zoneworks Compatible