



CLEVERTRONICS LP PREMIUM SUSTAINED LED TUBE EMERGENCY BATTEN WITH MICROWAVE SENSOR & LED POD



PRODUCT INFORMATION

Catalogue Number	CBS1L2S-WG-MS
Description	Wide Body Wire Guard Batten with LED Tube and Sustained Emergency.
Construction	Powder Coated Steel
Mounting	Surface Mount
Dimensions L x W x H	666mm x 120mm x 110mm
Operating Mode	Sustained/Combined Non-Maintained. On/off control of the LED tube via switched active input. Non-Maintained LED emergency function.
Testing System	Manual Test Switch
Diffuser	NA – Wire Guard
LED Tube(s)	1 x 600mm LED Tube 840 G13 880lm 50,000 Hours
Operating Voltage	240V, 50Hz
Charging Method	Intelligent current limited constant voltage charger
Emergency Lamp Source	2 x 3W LED (Lifetime warranty on the lamp head and loom assembly) No dome cover required
IP Rating	IP20
Operating Temperature	10° to 40°C
Power Consumption	9W (Lamps on) 1W (Lamps Off)
AS2293 Classification	C ₀ = D40 C ₉₀ = D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
3170025	Lamp, LED Tube 8W 4000K
1100640	Lamp, Lifelight Pro Head and Heatsink
1120320	Lamp Holder T8
250070	Wire Guard 14/18W Wide
2900012	Shanghai End Cap
1550050	Battery, LP 3.2V 3200 mAh 70mm Lead, No Bracket
8002530	PCA, LP Lifelight Driver ZWC, CT#10260-L3
1190116	Motion Sensor Assembly