



CLEVERTRONICS LP PREMIUM DIFFUSED BATTEN WITH INTEGRATED LED EMERGENCY



PRODUCT INFORMATION

Catalogue Number	CBS218S-DIF-CT
Description	2 X 18 Watt LP Diffused Batten With Premium Lithium LED Emergency
Construction	Powder Coated Steel body and Polycarbonate Lamp Holders
Mounting	Surface Mount
Dimensions L x W x H	666mm x 120mm x 110mm
Operating Mode	Sustained
Testing System	Clevertest
Charging Method	Intelligent current limited constant voltage charger
Ballast	Electronic , 2x18W, EEI=A3
Lamp(s)	T8 Cool white Tri-Phosphor 18W/840
Operating Voltage	240V
Power Consumption	39.3W (Lamps ON) 1.3W Standby
IP Rating	IP20
Operating Temperature	10° to 40°C
AS/NZ2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1310113	Ballast, VS FBC218 Electronic, 2 x 18W, EEI=A3
3100175	Lamp(s) T8 18W/840 COOLWHITE TUBE
1120320	Lamp Holder T8
2300060	Diffuser 14/18W wide
2750064	LP Batten Emergency End Cap (includes LED Assembly and Battery)
1550050	Battery, LP 3.2V 3200mAh 70mm lead,no BRKT.
8002530	PCA: LP Lifelight Driver, Zoneworks Compatible
8001730	Network, Clevertest Node