



CLEVERTRONICS LP PREMIUM DIFFUSED BATTEN WITH INTEGRATED LED EMERGENCY



PRODUCT INFORMATION

Catalogue Number	CBS236S-DIF-CT
Description	2 x 36 Watt LP Diffused Batten With Premium Lithium LED Emergency
Construction	Powder Coated Steel body and Polycarbonate Lamp Holders
Mounting	Surface Mount
Dimensions L x W x H	1274mm x 120mm x110mm
Operating Mode	Sustained
Testing System	Clevertest
Charging Method	Intelligent current limited constant voltage charger
Diffuser	Prismatic
Ballast	Electronic , 2x36W, EEI=A3
Lamp(s)	T8 Cool white Tri-Phosphor 36W/840
Operating Voltage	240V
Power Consumption	73W (Lamps ON) 1.0W Standby
IP Rating	IP20
Operating Temperature	10° to 40°C
AS/NZ2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1310226	Ballast, VS FBC236 2x36W EEI = A3
3100380	Lamp(s) T8 36W/840 COOLWHITE TUBE
1120320	Lamp Holder T8
2300110	Prismatic Diffuser
2750064	LP Batten Emergency End Cap (includes LED Assembly and Battery)
1550050	Battery, LP 3.2V 3200mAh 70mm lead,no BRKT.
8002530	PCA: LP Lifelight Driver, Zoneworks Compatible
8001730	Network, Clevertest Node