



CLEVERTRONICS LP LED TUBE WEATHERPROOF BATTEN (DLI)



PRODUCT INFORMATION

Catalogue Number	CWB1L2S-P-DLI
Description	LP Premium LED tube weatherproof batten with LED emergency POD
Construction	Polycarbonate Base and Diffuser with powder coated Metal Gear Tray and Tamper Proof Stainless Steel Clips
Mounting	Surface mount
Dimensions L x W x H	720mm x 160mm x 105mm
Operating Mode	Sustained
Testing System	DLI compatible
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Lamp(s)	1 x 600mm LED tube, Col. 840, 8W/880 lm per tube, 50,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	9 Watts (lamps ON), 1.0 Watts (lamps OFF)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40
Impact Rating	IK08

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery, LP 3.2V 3200mAh 70mm lead, no Bracket
3170025	LED TUBE 8W 4000K, 0.6m, 60°C
1120030	Lampholder, T8, T/S W'proof & Exit
2750370	LP WP Batten Lifelight POD & Battery
CLIFE-CKIT-2LED-WB	Lifelight, Control Only, WBatten, LP
8002200	PCA:DLI Node, #CT10410-A3