



CLEVERTRONICS 2 x 18W DIFFUSED BATTEN WITH MICROWAVE MOTION SENSOR CONTROL



PRODUCT INFORMATION

Catalogue Number	FBS218-DIF-A2-MS
Description	2 x 18 Watt Diffused Batten with Microwave Sensor Control On/Off function only with factory pre-set on time after last presence detection.
Construction	Powder Coated Steel body
Mounting	Surface Mount
Dimensions L x W x H	616mm x 115mm x 108mm
Operating Mode	240VAC
Diffuser	Prismatic
Ballast	High Frequency Electronic Ballast EEI = A2 and pre-heating function
Sensor	360° Microwave Motion Detector. Specify programmable or Non-programmable.
Lamp(s)	T8 18W/840 Cool White Tri-Phosphorous
Operating Voltage	240V
Power Consumption	39 Watts (5.7W Standby)
IP Rating	IP20
Operating Temperature	10° to 40°C

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1310075	Ballast, Philips HF-P 2x14-35W EEI =A2
3100175	Lamp(s) T8 18W/840 COOLWHITE TUBE
1120320	Lamp Holder T8
2300110	Prismatic Diffuser
2900012	Shanghai End Caps
1190116	Sensor: Microwave Motion Sensor Assembly



Typical Sensor Location: 2 x 18W Batten



NOTE: Diffuser not shown to display sensor.

Sensor location may vary between batten sizes.
Sensors can be ordered in Programmable or Non-programmable version.
Programmable sensors utilize a hand held device to upload operation parameters.