



CLEVERTRONICS ARGONAUT LED WEATHERPROOF BATTEN



PRODUCT INFORMATION

Catalogue Number	FWB4LED-P
Description	LED Weatherproof Batten
Construction	Polycarbonate Base (RAL7035), Polycarbonate Diffuser and Captive Stainless Steel Clips
Diffuser	Opal Polycarbonate
Mounting	Surface Mount via direct fixing to ceiling or via stainless steel clips
Dimensions L x W x H	1169mm(L) x 120mm(W) x 108mm(H)
Operating Mode	240 Volt
Lamp(s)	LED strip module, 4,000°K, 50,000h product life [L70, Ta 40°C] Ra>80
Driver	OSRAM OT FIT, 50,000hr
Operating Voltage	240V, 50 Hz
Total lumen output	4125lm @96lm/W
Power Consumption	43 Watts (PF = 0.95)
IP Rating	IP66
Operating Temperature	-20°C to +40°C
Impact Rating	IK08

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
31xxxxx	LED strip 4,000°K with gear tray
1330030	OSRAM OT FIT LED Driver SELV

FWB4LED-P



The Argonaut LED Weatherproof Batten is a weather proof, vandal resistant and dust proof IP66 rated LED luminaire, suitable for most commercial and industrial applications. It is particularly suited for underground car parks, where its distribution ensures that it provides good uniformity and illuminance levels at wide mounting centres. The LED modules used within the Argonaut LED Weatherproof Batten are easily replaceable, allowing for easy maintenance and a reduced life cycle cost. By using LEDs, the luminaire has a long expected lifetime and is ideal for environments where maintenance may be difficult.

Applications:

Carparks, Stairwells, Warehouses, Schools, Hospitals, Public Transit. Stadiums

