

## CLEVERTRONICS L10 DIFFUSED BATTEN WITH INTEGRATED LED EMERGENCY



### PRODUCT INFORMATION

Catalogue Number	LBS136S-DIF-A2
Description	1 X 36 Watt Diffused Batten With L10 Optimum Lithium LED Emergency
Construction	Powder Coated Steel body and Polycarbonate Lamp Holders
Mounting	Surface Mount
Dimensions L x W x H	1266mm x 120mm x 110mm
Operating Mode	Sustained
Testing System	Manual Test Switch
Charging Method	Intelligent current limited constant voltage charger
Ballast	Electronic , 1x36W, EEI=A2
Lamp(s)	T8 Cool white Tri-Phosphor 36W/840
Operating Voltage	240V
Power Consumption	36.4W (39W max during 16 hour charge)
IP Rating	IP20
Operating Temperature	1° to 40°C
AS/NZ2293 Classification	C <sub>0</sub> =D63 C <sub>90</sub> =D63

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1310210	Ballast, HF-P, 1 x 36W, EEI=A2
3100380	Lamp(s) 36W/840 T8 Cool White
2300060	Prismatic Diffuser (Acrylic)
LLIFE-PRO-CKIT	Driver, PCA:L10/LP Lifelight Pro, Zoneworks Compatible
1530050	Battery L10, 2.5Ah, 70mm lead, no bracket