



CLEVERTRONICS L10 I x 36W WIRE GUARD BATTEN WITH LED EMERGENCY



PRODUCT INFORMATION

Catalogue Number	LBS136S-WG-A2-CT
Description	2 x 36 Watt Wire Guard Batten with LED Emergency
Construction	Powder Coated Steel body with Polycarbonate lamp holders.
Mounting	Surface Mount
Dimensions L x W x H	1266mm x 115mm x 108mm
Operating Mode	Sustained
Testing System	Clever-test
Charging Method	Intelligent current limited constant voltage charger
Diffuser	NA – Wire Guard
Ballast	Electronic , 1x36W, EEI=A2
Lamp(s)	T8 Cool White Tri-Phosphorous 36W/840
Emergency Lamp Source	2 x 3W LED (Lifetime warranty on the lamp head and loom assembly) No dome cover required
Operating Voltage	240V
Power Consumption	36.4 Watts (lamps ON) .4 Watts (lamps OFF)
IP Rating	IP20
Operating Temperature	0° to 40°C
AS2293 Classification	C0=D63 C90=C63

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1310210	Ballast, HF-P, 1 x 36W, EEI=A2
3100380	Lamp(s) 36W/840 T5 Cool White
1120320	Lamp Holder T8 with Cover
2500110	Diffuser 28/36W Wide
2900012	End Caps
LLIFEE-PRO-CKIT-CT-NP	Lifelight Pro,ControlOnly, Batten,CT,L10
3760210	Emergency End Cap control
8001730	Clevertest Node