

CLEVERTRONICS L10 WIRE GUARD PRO BATTEN (Zoneworks)



PRODUCT INFORMATION

Catalogue Number	LBS136S-WG-A2-ZW
Description	1 x 36 Watt L10 Optimum wired guard PRO batten with LED emergency POD
Construction	Powder coated steel body and ABS/polycarbonate end caps
Mounting	Surface mount
Dimensions L x W x H	1265mm x 160mm x 110mm
Operating Mode	Sustained
Testing System	Zoneworks computerised testing
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Wire Guard
Ballast	Electronic, EEI=A2
Lamp(s)	T8 Cool White Tri-Phosphorous 36W/840
Operating Voltage	240V AC; 50Hz
Power Consumption	36 Watts (lamps ON) 0.4 Watts (lamps OFF)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D63 C ₉₀ =D63

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	BATTERY:L10 3.3V 2.5AH 70mm lead,noBRKT
LLIFE-PRO-CKIT-ZW-NP	LifelightPro,ControlOnly,Batten, ZW, L10
1310210	1x36w Electronic Ballast, A2
3100380	36w/840 Coolwhite Lamp
1120320	LAMPHOLDER, t/s T8 Sabre Battens, 2 Part
8001450	PCA:Powerline Node ZW, #CT10310-A6

ZONEWORKS

L10™ OPTIMUM
LITHIUM BATTERY RANGE

Version: October 2016-I

www.clevertronics.com.au