



CLEVERTRONICS 2 x 14W DIFFUSED BATTEN WITH INTEGRATED LED EMERGENCY



PRODUCT INFORMATION

Catalogue Number	LBS214S-DIF-A2-ZW
Description	2 x 14 Watt Diffused Batten with Emergency LED POD
Construction	Powder Coated Steel body with Polycarbonate lamp holders.
Mounting	Surface Mount
Dimensions L x W x H	666mm x 120mm x 110mm
Operating Mode	Sustained
Testing System	Zoneworks Computerized Testing
Charging Method	Intelligent current limited constant voltage charger
Diffuser	Prismatic
Ballast	Electronic , 2x14-35W, EEI=A2
Lamp(s)	T5 Cool White Tri-Phosphorous 14W/840
Operating Voltage	240V
Power Consumption	37.5 Watts (lamps ON) .7W (lamps OFF)
IP Rating	IP20
Operating Temperature	10° to 40°C
AS2293 Classification	C0=D63 C90=C63

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1310075	Ballast, Philips HF-P, 2 x 14-35W, EEI=A2
3100010	Lamp(s) 14W/840 T5 COOLWHITE TUBE
1120215	Lamp Holder T5
1120195	Lamp Holder Adaptor 14W T8>T5
2300060	Diffuser 14/18W wide
2900012	End Caps
8001450	Network: Zoneworks Powerline Node
3760210	Emergency End Cap control