

CLEVERTRONICS L10 DIFFUSED BATTEN WITH INTEGRATED LED EMERGENCY



PRODUCT INFORMATION

Catalogue Number	LBS218S-DIF-A2
Description	2 X 18 Watt Diffused Batten With Premium L10 Lithium LED Emergency
Construction	Powder Coated Steel body and Polycarbonate Lamp Holders
Mounting	Surface Mount
Dimensions L x W x H	666mm x 120mm x 110mm
Operating Mode	Sustained
Testing System	Manual Test Switch
Charging Method	Intelligent current limited constant voltage charger
Ballast	Electronic , 2x18W, EEI=A2
Lamp(s)	T8 Cool white Tri-Phosphor 18W/840
Operating Voltage	240V
Power Consumption	35W (Lamps On) (0.4W Standby)
IP Rating	IP20
Operating Temperature	10° to 40°C
AS/NZ2293 Classification	C ₀ =D63 C ₉₀ =D63

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1310115	Ballast, HF-P, 2 x 18W, EEI=A2
3100175	Lamp(s) T8 18W/840 COOLWHITE TUBE
2300060	Prismatic Diffuser (Acrylic)
8002390	Driver, PCA:L10/LP Lifelight Pro, Zoneworks Compatible 400mA Output
3760210	Emergency End Cap control