



## CLEVERTRONICS 2 x 28W DIFFUSED BATTEN WITH LED EMERGENCY



### PRODUCT INFORMATION

Catalogue Number	LBS228S-DIF-A2
Description	2 x 28 Watt Wire Guard Batten with LED Emergency
Construction	Powder Coated Steel body with Polycarbonate lamp holders.
Mounting	Surface Mount
Dimensions L x W x H	1274mm x 120mm x 110mm
Operating Mode	Sustained
Testing System	Manual Test Switch
Charging Method	Intelligent current limited constant voltage charger
Diffuser	Prismatic
Ballast	Electronic , 2 x 28W, EEI=A2
Lamp(s)	T5 Cool White Tri-Phosphorous 28W/840
Operating Voltage	240V
Power Consumption	59.4 Watts (lamps ON) .4 Watts (lamps OFF)
IP Rating	IP20
Operating Temperature	10° to 40°C
AS2293 Classification	C0=D63 C90=C63

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1310075	Ballast, HF-P 2 x 14-35W, EEI=A2
3100210	Lamp(s) 28W/840 T5 COOLWHITE TUBE
1120215	Lamp Holder T5
1120212	Lamp Holder Adaptor 14W T8>T5
2300110	Prismatic Diffuser 28W Wide
2900012	End Caps
3760210	Emergency End Cap control