

CLEVERTRONICS I x 36W DIFFUSED BATTEN WITH LED EMERGENCY



PRODUCT INFORMATION

Catalogue Number	LBS236S-DIF-A2-ZW
Description	2 x 36 Watt Diffused Batten with LED Emergency
Construction	Powder Coated Steel body with Polycarbonate lamp holders.
Mounting	Surface Mount
Dimensions L x W x H	1266mm x 115mm x 108mm
Operating Mode	Sustained
Testing System	Zoneworks Computerized Testing
Charging Method	Intelligent current limited constant voltage charger
Diffuser	Prismatic
Ballast	Electronic , 2x36W, EEI=A2
Lamp(s)	T8 Cool White Tri-Phosphorous 36W/840
Emergency Lamp Source	2 x 3W LED (Lifetime warranty on the lamp head and loom assembly) No dome cover required
Operating Voltage	240V
Power Consumption	68.7 Watts (lamps ON) .7 Watts (lamps OFF)
IP Rating	IP20
Operating Temperature	10° to 40°C
AS2293 Classification	C0=D63 C90=C63

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1310224	Ballast, Philips HF-P, 2 x 36W, EEI=A2
3100380	Lamp(s) 36W/840 T8 Cool White
1120320	Lamp Holder T8 with Cover
2300110	Diffuser 28/36W Wide
2900012	End Caps
3760210	Emergency End Cap control
8001450	Network, Zoneworks Powerline Node