

CLEVERTRONICS L10 OPTIMUM LIFELIGHT PRO CYLINDER SURFACE MOUNT EMERGENCY (DLI)



PRODUCT INFORMATION

Catalogue Number	LLIFE-PRO-SMC-DLI
Description	Lifelight PRO, High Performance, Cylinder Surface Mount Emergency Light with Lithium Battery Technology
Mounting	Surface Mount
Dimensions L x W x H	128mm (D), 252mm (L)
Ceiling hole cut-out	N/A
Minimum ceiling depth	N/A
Operating Mode	Non-Maintained
Testing System	DLI Compatible
Charging Method	Intelligent current limited constant voltage charger
Lamps(s)	2 x 3W LED (Lifetime warranty on the lamp head and loom assembly) No dome cover required
Operating Voltage	240V 50Hz
Power Consumption	0.4W (standby) 2.2W (max during 16 hour charge)
IP Rating	IP20
Impact Rating	N/A
Operating Temperature	1° to 40°C (Ambient)
AS/NZ2293 Classification	C ₀ =D50 C ₉₀ =D50

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1100830	Lamps: 2 x 3W LED Round Head Assembly - White
1530230	Battery: 3.3V 5Ah.Li-ion, 200mm lead with Bracket
LLIFE-PRO-CKIT-NP	PCA: Lifelight Pro Control Gear
8002200	PCA: DLI Node, #CT10410-A3

