



CLEVERTRONICS L10 PROFESSIONAL WEATHERPROOF BATTEN



Gen 1



Gen 2

PRODUCT INFORMATION

Catalogue Number	LWB118S-P-A2-CT
Description	1 x 18 Watt L10 Optimum Weatherproof Batten with LED Emergency POD
Construction	Polycarbonate Base and Diffuser with Powdercoated Metal Gear Tray and Tamper proof Stainless Steel clips
Mounting	Surface Mount
Dimensions L x W x H	720mm x 160mm x 105mm
Weight	2.6kg
Operating Mode	Sustained
Testing System	Clevertest
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Ballast	High Frequency Electronic Ballast EEI= A2
Lamp(s)	T8 Cool White Tri-Phosphorous 18W/840
Operating Voltage	240V AC; 50Hz
Power Consumption	19 Watts (Lamps ON) 0.4 Watts (Lamps OFF)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D63 C ₉₀ =D50 (Gen 1) C ₀ =D80 C ₉₀ =D80 (Gen 2)
Impact Rating	IK08

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	BATTERY:L10 3.3V 2.5AH 70mm lead,noBRKT
1310100	1x18w Electronic Ballast, A2
LLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,L10, NP
8001730	PCA:STU t/s Clever-test, #CT10080-A5

