



CLEVERTRONICS L10 PROFESSIONAL WEATHERPROOF BATTEN



Gen 1



Gen 2

PRODUCT INFORMATION

Catalogue Number	LWB228S-P-A2
Description	2 x 28 Watt L10 Optimum Professional Weatherproof Batten with LED Emergency POD, Enabled with Clevertest Plus
Construction	Polycarbonate Base and Diffuser with Powdercoated Metal Gear Tray and Tamper proof Stainless Steel clips
Mounting	Surface Mount
Dimensions L x W x H	1265mm x 160mm x 110mm
Operating Mode	Sustained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Ballast	High Frequency Electronic Ballast EEI= A2
Lamp(s)	T5 Cool White Tri-Phosphorous 28W/840
Operating Voltage	240V AC; 50Hz
Power Consumption	63 Watts (Lamps ON) 0.4 Watts (Lamps OFF)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D63 C ₉₀ =D50 (Gen 1) C ₀ =D80 C ₉₀ =D80 (Gen 2)
Impact Rating	IK08

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	BATTERY:L10 3.3V 2.5AH 70mm lead,noBRKT
1310075	2x14-35w Elect Ballast Multiwatt, A2
LLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,L10, NP

