



CLEVERTRONICS LP PREMIUM WIRE GUARD BATTEN WITH INTEGRATED LED EMERGENCY



PRODUCT INFORMATION

| | |
|--------------------------|---|
| Catalogue Number | CBS236S-WG-CT |
| Description | 2 x 36 Watt LP Wire Guard Batten With Premium Lithium LED Emergency |
| Construction | Powder Coated Steel body and Polycarbonate Lamp Holders |
| Mounting | Surface Mount |
| Dimensions L x W x H | 1274mm x 120mm x110mm |
| Operating Mode | Sustained |
| Testing System | Clevertest |
| Charging Method | Intelligent current limited constant voltage charger |
| Ballast | Electronic , 2x36W, EEI=A3 |
| Lamp(s) | T8 Cool white Tri-Phosphor 36W/840 |
| Operating Voltage | 240V |
| Power Consumption | 73W (Lamps ON) 1.0W Standby |
| IP Rating | IP20 |
| Operating Temperature | 10° to 40°C |
| AS/NZ2293 Classification | C ₀ =D40 C ₉₀ =D40 |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|---|
| 1310226 | Ballast, VS FBC236 2x36W EEI = A3 |
| 3100380 | Lamp(s) T8 36W/840 COOLWHITE TUBE |
| 1120320 | Lamp Holder T8 |
| 2500130 | Wire Guard 28/36W Wide |
| 2750064 | LP Batten Emergency End Cap (includes LED Assembly and Battery) |
| 1550050 | Battery, LP 3.2V 3200mAh 70mm lead,no BRKT. |
| 8002530 | PCA: LP Lifelight Driver, Zoneworks Compatible |
| 8001730 | PCA: Clevertest Node |