



## CLEVERTRONICS LP PREMIUM CLEVERFIT PRO LED THEATRE EXIT (ZONWORKS)



### PRODUCT INFORMATION

Catalogue Number	CCFPRO-TH-ZW-R
Description	LED LP Premium Cleverfit Pro Theatre Exit, 24 metre viewing Distance
Construction	Fire-retardant PC/ABS body with Polycarbonate Diffusers
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	367mm x 72mm x 214mm
Operating Mode	Maintained
Testing System	Zoneworks Computerised Testing
Charging Method	Intelligent current limited constant voltage charger
Diffuser	Theatre Mask (must specify diffuser combination)
Lamp(s)	2 x 1W LED, 100,000 hours
Operating Voltage	240V 50Hz
Power Consumption	3.5W Standby (3.3W during first 16hr charge)
IP Rating	IP20
Operating Temperature	1° to 40°C
AS/NZS2293 Classification	NA – Theatre Mask

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550130	Battery: 3.2 Volt 1.5Ah Li-ion
8002550	PCA: CCFPRO Driver No Sw.A, #CT10270-L1
8002250	PCA: CPRO LED Board w Loom, #CT10172-A1
8001450	PCA: Zoneworks Powerline Node, #CT10310-A6

