

CLEVERTRONICS LP ARGONAUT PRO MAINTAINED EMERGENCY LED WEATHERPROOF BATTEN WITH INTEGRAL BATTERIES



PRODUCT INFORMATION

Catalogue Number	CWB4LEDM-P-IB-PRO-ZW
Description	LP Premium High Performance Narrow Body, 1200mm, LED Maintained Emergency Weatherproof Batten with Integral Batteries
Construction	Glass Fibre Reinforced (GRP) Base, polycarbonate diffuser with powder coated metal gear tray and stainless steel clips
Mounting	Surface Mount via direct fixing to ceiling or via stainless steel clips
Dimensions L x W x H	1282mm x 100mm x 101mm
Operating Mode	Maintained
Testing System	Zoneworks computerised testing
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Ballast	BAG SELV
Lamp(s)	2 x LED module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Total lumen output	4212 lm @ 114m/W (based on the non-emergency version)
Power Consumption	39 Watts (lamps ON), 1.9 Watts (lamps OFF)
IP Rating	IP66 (Polyurethane gasket, poured in one piece)
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D100 C ₉₀ =D40
Diffuser Impact Rating	IK08

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550260	BATT:LP 6.4V 3200mAh 200mm lead.SBS.
8002670	PCA:40 LED Strip 600mm for Argonaut PRO
1330010	LED Driver - Argonaut Pro
8001460	PCA:PwrIn Node ZW Horizontal #CT10310-A6
CCPLED-48V95C-CKIT	LED Power Pack, 48V 95mA, LP
CCPLED-48V95C-CKIT-ZW	LED Power Pack, 48V 95mA, ZW, LP (Note: includes Zoneworks node)

ZONEWORKS

LP™ PREMIUM
LITHIUM BATTERY RANGE

Version: June 2016-I

www.clevertronics.com.au

 **Clevertronics®**
Emergency lighting innovation