


T8 LP™ PREMIUM SABRE WIRE GUARD BATTEN



Thermal isolation pod

UP TO TWICE THE BATTERY LIFE - Complete with LP™ Premium lithium iron phosphate technology.

WIDE BODY - To cover junction boxes and provides ample space for heat generating components.

TESTING OPTIONS - Clevertest™, DLI compatible and Zoneworks® computerised testing options available in our Premium range.

The LP™ Premium wire guard batten is a non-maintained, C0=D40 C90=D40 classified surface mounted luminaire. Its features include an LP™ Premium lithium battery which is housed in a thermal isolation pod at the end of the batten.

UP TO
TWICE
THE
BATTERY LIFE

As the pod is external to the batten, the battery is protected from high temperatures that are normally found within the batten thereby extending battery life. This combination of lithium battery and thermally stable housing provides for up to twice the battery life, when compared to Premium NiCd products. Maintenance cost savings of up to 50% are achieved as there are less failures and hence labour costs over time.

UP TO
50%
MAINTENANCE
SAVINGS

The battery is a lithium iron phosphate battery which contains no known carcinogens or heavy metal contaminants (unlike Nickel Cadmium and Nickel Metal Hydride batteries) and as they have twice the battery life they are the more environmentally responsible option.

LP™ Premium lithium battens are available in either diffused, wire guard or IP65 weatherproof combinations, which address most emergency lighting applications including basement car parks, warehouses, fire stairs, industrial sites, commercial and public areas.

HAWKEYE IS NOW AVAILABLE IN THE LP™ PREMIUM BATTEN RANGE

UP TO
88%
ENERGY
SAVINGS*

The HAWKEYE microwave movement sensor is integrated into the body of the batten and is designed to turn off the batten's light source when no presence is detected by the sensor. The ability to turn the light source off when not required means less running time, saving energy and maintenance costs and money.



*Based on 2x36W batten running 2 hours on per day with Hawkeye microwave sensor.

T8 LP™ PREMIUM SABRE WIRE GUARD BATTEN

SEGMENT - LAMP TYPE	PART NUMBER - STANDARD 240V	
Fluorescent Lamp	A2 Electronic Ballast	DLI Ballast
240V 1x18W	FBS118-WG-A2	FBS118-WG-DB
240V 2x18W	FBS218-WG-A2	FBS218-WG-DB
240V 1x36W	FBS136-WG-A2	FBS136-WG-DB
240V 2x36W	FBS236-WG-A2	FBS236-WG-DB

SPECIFICATIONS - STANDARD 240V	
Fluorescent Lamp	L x W x H (mm)
1x18W	630 x 120 x 110
2x18W	630 x 120 x 110
1x36W	1238 x 120 x 110
2x36W	1238 x 120 x 110

SEGMENT - LAMP TYPE	PART NUMBER & TESTING OPTIONS - LP EMERGENCY BATTEN - NON MAINTAINED EMERGENCY POD				
A2 Electronic Ballast	Single-point	Clevertest™	DATA	DLI*	Zoneworks
LP 1x18W SUSTAINED	CBS118S-WG-A2	CBS118S-WG-A2-CT	CBS118S-WG-A2-DATA	CBS118S-WG-A2-DLI	CBS118S-WG-A2-ZW
LP 2x18W SUSTAINED	CBS218S-WG-A2	CBS218S-WG-A2-CT	CBS218S-WG-A2-DATA	CBS218S-WG-A2-DLI	CBS218S-WG-A2-ZW
LP 1x36W SUSTAINED	CBS136S-WG-A2	CBS136S-WG-A2-CT	CBS136S-WG-A2-DATA	CBS136S-WG-A2-DLI	CBS136S-WG-A2-ZW
LP 2x36W SUSTAINED	CBS236S-WG-A2	CBS236S-WG-A2-CT	CBS236S-WG-A2-DATA	CBS236S-WG-A2-DLI	CBS236S-WG-A2-ZW

SEGMENT - LAMP TYPE	PART NUMBER & TESTING OPTIONS - LP EMERGENCY BATTEN - NON MAINTAINED EMERGENCY POD				
A1 DLI Electronic Ballast	Single-point	Clevertest™	DATA	DLI*	Zoneworks
LP 1x18W SUSTAINED	CBS118S-WG-DB	CBS118S-WG-DB-CT	CBS118S-WG-DB-DATA	CBS118S-WG-DB-DLI	CBS118S-WG-DB-ZW
LP 2x18W SUSTAINED	CBS218S-WG-DB	CBS218S-WG-DB-CT	CBS218S-WG-DB-DATA	CBS218S-WG-DB-DLI	CBS218S-WG-DB-ZW
LP 1x36W SUSTAINED	CBS136S-WG-DB	CBS136S-WG-DB-CT	CBS136S-WG-DB-DATA	CBS136S-WG-DB-DLI	CBS136S-WG-DB-ZW
LP 2x36W SUSTAINED	CBS236S-WG-DB	CBS236S-WG-DB-CT	CBS236S-WG-DB-DATA	CBS236S-WG-DB-DLI	CBS236S-WG-DB-ZW

*DLI battens are listed with the LP LED D40 Emergency Pod with DLI compatible emergency control packs.

SPECIFICATIONS - LP PREMIUM WIRE GUARD EMERGENCY BATTEN WITH NON MAINTAINED LED EMERGENCY POD				
Fluorescent Lamp	L x W x H (mm)	C0	C90	
1x18W	666 x 120 x 110	D40	D40	
2x18W	666 x 120 x 110	D40	D40	
1x36W	1274 x 120 x 110	D40	D40	
2x36W	1274 x 120 x 110	D40	D40	

240V AND LP PREMIUM

Wide body fluorescent batten. Wire guard or diffused body options to choose from.

240V and LP PREMIUM emergency versions available. T8, 840 Tri Phosphor fluorescent lamps included.

TESTING OPTIONS

 Exit and Emergency luminaires automatically test every six months.

 A real-time, automatic monitoring and testing facility for emergency luminaires.

SPACING TABLE & MOUNTING HEIGHTS													
Classification	2.1m	2.4m	2.7m	3m	3.3m	3.6m	4m	5m	6m	7m	8m	10m	15m
D40	16.7	17.4	18.0	18.6	19.1	19.6	20.1	21.3	22.1	22.7	23.0	23.1	19.4

Based on minimum light level of 0.2 lux

Version: October 2014-4

Please check our website for your closest Clevertronics office and local representative. Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.

www.clevertronics.com.au

