

CLEVERFIT PRO EXIT



Modern and Slimline Architectural Exit

The Cleverfit PRO Exit offers a practical solution in a slimline, architecturally pleasing design. The tamper resistant cover makes it possible to include all diffuser combinations in one box for single or double sided applications.

With a slide connect steel bracket that can be both ceiling or wall mounted, it is easy to see why the Cleverfit PRO is a market leader.

Applications

- | | |
|---|--|
|  Office Buildings |  Shopping Centres |
|  Showrooms |  Retail Outlets |
|  Theatres |  Apartments |



Features and Benefits

- AS/NZS 2293.3 compliant
- Low 2.8W standby power consumption
- Wall and ceiling mount with easy slide connect
- All directional decals in one box
- Lithium Iron Phosphate or Nanophosphate® battery
- Clevertest Plus System compatible
- Theatre version available



CLEVERFIT PRO EXIT

ORDERING INFORMATION		LP	L10
PART NO.	Standard	CCFPRO	LCFPRO
	Clevertest Plus System Compatible	Yes	Yes
	DALI	CCFPRO-DALI	LCFPRO-DALI
	Zoneworks® XT Hive	CCFPRO-HV	LCFPRO-HV
	Theatre Version	CCFPRO-TH	LCFPRO-TH
Carton Quantity	5		
Weight - single (carton)	2.5kg (15.0kg)		
Dimensions (L x W x H)	367mm x 72mm x 214mm		
Directional Options	All Directional Inserts Included (Excluding theatre versions)		
Directional Options (Theatre Only)	Add Suffix to Part Number, -DS Double Sided, -R Pictograph, L (Left) or R (Right) ie. CCFPRO-TH-DS-RR		

* for additional variants please refer to the Clevertronics Product Guide or website.

POWER, LAMPS AND BATTERY	LP	L10
Power Consumption (Standby / Max)	2.8W / 3.9W	
Lamp(s)	100,000 Hour LED	
Battery	Lithium Iron Phosphate	Lithium Nanophosphate®
Voltage (V) / Capacity (mAh)	3.2V / 1100mAh	3.3V / 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage	

TECHNICAL SPECIFICATIONS	
Operating Mode	Maintained
Voltage (V) Frequency (Hz)	220-240V(50Hz)
Construction - Body / Diffuser	PC-ABS / PC
Viewing Distance	24m
Mounting Type	Wall & Ceiling (Single & Double Sided)
Operating Temperature	1°C to 40°C
Ingress Protection Rating (IP)	IP20

CLASSIFICATION	LP	L10
C0	E2.5	E2.5
C90	B12.5	B12.5

SPARE PARTS	LP	L10
Battery	1550105	1530030
Lamp Bar	8002710	8002710
DALI Node	8003060	8003060
Zoneworks® XT Hive Node	8003190	8003190
Diffuser	2360192	2360192

ACCESSORIES	LP	L10
Cantilever Bracket	CLVRBRT-CFPRO	CLVRBRT-CFPRO
Wireguard (Wall Mount)	2530053	2530053
Wireguard (Ceiling Mount)	2530110	2530110

SPACING TABLE AND MOUNTING HEIGHTS – AS/NZS 2293.1:2018 (MINIMUM LIGHT LEVEL OF 0.2 LUX)									
Classification	2.1m	2.4m	2.7m	3.0m	3.3m	3.6m	4.0m	4.5m	5.0m
E2.5	5.4	5.6	5.8	5.8	5.8	0.0	0.0	0.0	0.0
B12.5	6	6.4	6.8	7.1	7.4	7.6	7.9	8.2	8.4

For 1 lux and AS/NZS 2293.1:2005 spacing tables please visit:
<https://clevertronics.com.au/spacing-tables/>

Based on minimum light level of 0.2 lux. Maximum allowed mounting height is 2.7m but for exceptions see AS/NZS 2293.1. Spacing classifications do not apply for theatre versions.

*Warranty information located at:
<https://clevertronics.com.au/warranty-statement/>



Dimensions (mm)

clevertronics.co.nz
clevertronics.com.au

195 Chesterville Road, Moorabbin VIC 3189
P +61 3 9559 2700 F +61 3 9559 2799 E info@clevertronics.com.au

Clevertronics is committed to continuously improving its products. All features and specifications are subject to change without prior notice. CT-BRO-ANZ-CLEVERFITPRO-EX-001