



CLEVERTRONICS LP PREMIUM DIFFUSED BATTEN WITH INTEGRATED LED EMERGENCY



PRODUCT INFORMATION

Catalogue Number	CBS118S-DIF-A2-DLI
Description	1 X 18 Watt LP Diffused Batten With 4 Hour Premium Lithium LED Emergency
Construction	Powder Coated Steel body and Polycarbonate Lamp Holders
Mounting	Surface Mount
Dimensions L x W x H	666mm x 120mm x 110mm
Operating Mode	Sustained
Testing System	DLI Compatible Testing
Charging Method	Intelligent current limited constant voltage charger
Ballast	Electronic , 1x18W, EEI=A2
Lamp(s)	T8 Cool white Tri-Phosphor 18W/840
Operating Voltage	240V
Power Consumption	19W (22W max during 16 hour charge)
IP Rating	IP20
Operating Temperature	10° to 40°C
AS/NZ2293 Classification	C ₀ =D40 C ₉₀ =C40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1310100	Ballast, HF-P, 1 x 18W, EEI=A2
3100175	Lamp(s) T8 18W/840 COOLWHITE TUBE
2300060	Prismatic Diffuser (Acrylic)
110083X	2 x 3W LED Assembly (L10/LP Lifelight PRO GDP PCA)
1550050	Battery, LP 3.2V 3200mAh 70mm lead,no BRKT.
800239X	Driver, PCA:L10/LP Lifelight Pro, Zoneworks Compatible 400mA Output
8002200	Network: DLI Node