



CLEVERTRONICS LP 600MM (2FT) NON-MAINTAINED BATTEN REPLACEMENT



PRODUCT INFORMATION

Catalogue Number	CBS2N-CT
Description	LP Premium 600mm (2ft) Non-Maintained Bare Batten Replacement Utilising the Lifelight - High Performance, Emergency Light with Premium Lithium Battery Technology Enabled with Clevertest Plus
Construction	Powder coated Steel body and ABS/Polycarbonate End Caps
Mounting	Surface Mount
Dimensions L x W x H	610mm x 110mm x 50mm
Operating Mode	Non-maintained
Testing System	Clevertest Plus
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	1 LED (Lifetime warranty on the lamp head and loom assembly) No dome cover required
Operating Voltage	240V AC; 50Hz
Power Consumption	1.0 Watts (Standby), 3.9 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550010	BATT:LP 3.2V 3200mAh 200mm lead,BRKT.
1100930	CLIFE Head Assembly, Round, 1LED
CLIFE-CKIT-NP	Lifelight, Control Only, LP, No Plug

