



## CLEVERTRONICS LP 600mm (2ft) non-maintained bare batten replacement



### PRODUCT INFORMATION

Catalogue Number	CBS2N
Description	LP 600mm (2ft) non-maintained bare batten replacement utilising the Lifelight - High Performance, Emergency Light with Premium Lithium Battery Technology
Mounting	Surface Mount
Dimensions L x W x H	610mm x 110mm x 50mm
Operating Mode	Non-Maintained
Testing System	Manual Test Switch
Ballast	N/A
Charging Method	Intelligent current limited constant voltage charger
Lamps(s)	1 LED (Lifetime warranty on the lamp head and loom assembly) No dome cover required
Operating Voltage	240V 50Hz
Power Consumption	1.0W Standby (3.9W during first 16hr charge)
IP Rating	IP20
Impact Rating	N/A
Operating Temperature	1° to 40°C (Ambient)
AS/NZ2293 Classification	C <sub>0</sub> =D40 C <sub>90</sub> =D40

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1100930	1 LED Round Head Assembly & Ring - White
1550010	Battery, LP 3.2V 3.2Ah, Li-ion, 200mm lead with Bracket
CLIFE-CKIT	Lifelight, Control Gear Only, LP Lithium

