



CLEVERTRONICS LP 1200MM (4FT) NON-MAINTAINED BATTEN REPLACEMENT (Clevertest)



PRODUCT INFORMATION

Catalogue Number	CBS4N-CT
Description	LP Premium 1200mm (4ft) Non-Maintained Bare Batten Replacement Utilising the Lifelight - High Performance, Emergency Light with Premium Lithium Battery Technology
Construction	Powder coated Steel body and ABS/Polycarbonate End Caps
Mounting	Surface Mount
Dimensions L x W x H	1220mm x 110mm x 50mm
Operating Mode	Non-maintained
Testing System	Clevertest Plus
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x 3W LED (Lifetime warranty on the lamp head and loom assembly) No dome cover required
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4 Watts (Standby), 4.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D63 C ₉₀ =D63

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
1100830	Lifelight Pro Head Assembly, Round
CLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,LP, NP

