



## CLEVERTRONICS LP CLEVERFIT PRO EXIT (Zoneworks)



### PRODUCT INFORMATION

Catalogue Number	CCFPRO-ZW
Description	LP Premium Cleverfit PRO Emergency Exit
Construction	Fire-retardant PC/ABS body with Polycarbonate Diffuser
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.5kg
Operating Mode	Maintained
Testing System	Zoneworks computerised testing
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x Duris E2 LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 3.5 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =E2.5 C <sub>90</sub> =B12.5
Viewing Distance	24m

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	BATT:LP 3.2V 1100mAh 260mm lead,no BRKT
8002920	PCA:CCF-Pro #CT10142-L8 CTP
8002710	PCA:DurisLED Strip Clvrft Pro CT10276-D1
8001450	PCA:Powerline Node ZW, #CT10310-A6

ZONEWORKS

**LP** LITHIUM IRON PHOSPHATE

PREMIUM

PROVEN PROJECT PERFORMANCE