

CLEVERTRONICS LP LED SUPALITE (ZONWORKS XTHIVE)



PRODUCT INFORMATION

Catalogue Number	CFLLED-HV
MIC	AUE02810010001
Description	LP Premium Supalite LED Flood Unit, Surface Mounted Emergency Light
Construction	Polycarbonate
Mounting	Surface Mounted. Supplied with flex and plug (the flex and plug can be removed to allow for a hard wired connection)
Dimensions L x W x H	Main enclosure - 282mm (W) x 137mm (H) x 64mm (D) Total height including LED Heads 225mm.
Weight	1.3kg
Operating Mode	Non-maintained
Testing System	Zoneworks XTHIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x LED Heads (adjustable), 185lm per lamp head
Operating Voltage	240V AC; 50Hz
Power Consumption	0.5 Watts (Standby), 3.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =N/A C ₉₀ =N/A

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
1100955	LED Flood Lamp Head Ass, Cable & Cnnctr.
8003190	PCA: RF Node CT10678-Ax internal antenna

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order