



## CLEVERTRONICS LP GIGANTOR EXIT (Zoneworks)



### PRODUCT INFORMATION

Catalogue Number	CGELED-80-WM-ZW-R
Description	LP Premium Wall Mount Gigantor Exit, 80 metre viewing Distance
Construction	Powder coated Metal Frame with Acrylic Diffuser
Mounting	Wall Mount, Single-Sided
Dimensions L x W x H	1305mm x 170mm x 560mm
Weight	21kg
Operating Mode	Maintained
Testing System	Zoneworks computerised testing
Battery	Lithium Iron Phosphate, 3.2V 6400mAh Lithium Iron Phosphate, 6.4V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Running Man (must specify diffuser combination)
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80 2 x 3W LED (Lifetime warranty on the Lamp head and loom Assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	23 Watts (Standby), 30 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D50 C <sub>90</sub> =D50
Viewing Distance	80m

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550290	BATT:LP 6.4V 3.2Ah.200mm lead.Stick.Brkt
CCPLED-38V120C-CKIT	LED Power Pack, 38V 120mA, LP
8001460	PCA:Pwrln Node ZW Horizontal #CT10310-A6
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
CLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,LP, NP
1100830	Lifelight Pro Head Assembly, Round
8001450	PCA:Powerline Node ZW, #CT10310-A6

