



## CLEVERTRONICS LP JUMBO LED EXIT UNIVERSAL MOUNT (Zoneworks)



### PRODUCT INFORMATION

Catalogue Number	CJELED-40-ZW
Description	LP Premium Jumbo Emergency Exit
Construction	Powder coated Metal Frame with Acrylic Diffuser
Mounting	Surface Mount
Dimensions L x W x H	630mm x 100mm x 320mm
Weight	7.3kg
Operating Mode	Maintained
Testing System	Zoneworks computerised testing
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All pictograph directional inserts included in the box (One box solution)
Lamp(s)	12 x High Intensity LED, Surface Mounted onto a Replaceable Lamp Bar - 100,000hrs
Operating Voltage	240V AC; 50Hz
Power Consumption	3.2 Watts (Standby), 5.6 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D6.3 C <sub>90</sub> =E3.2
Viewing Distance	40m

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550010	BATT:LP 3.2V 3200mAh 200mm lead,BRKT.
CJELED-40-CKIT-110	Jumbo LED Exit, Control Kit, LP
8002470	PCA:Duris E5 Strip for LJELED.CT10050-D1
8001450	PCA:Powerline Node ZW, #CT10310-A6

**ZONEWORKS****LP** LITHIUM IRON  
PHOSPHATE

PREMIUM

PROVEN PROJECT PERFORMANCE