

CLEVERTRONICS LP LIFELIGHT PRO SURFACE MOUNT EMERGENCY (Clevertest)



PRODUCT INFORMATION

Catalogue Number	CLIFE-2PRO-SMS-600-CT
Description	LP Premium Lifelight PRO, High Performance, Surface Mount Twin Emergency Light with Lithium Battery Technology
Construction	Powder Coated Metal Frame
Mounting	Surface Mount and can also be chain suspended
Dimensions L x W x H	610mm x 110mm x 50mm
Operating Mode	Non-maintained
Testing System	Clevertest
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x 3W LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.8 Watts
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D125 C ₉₀ =D125

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
LLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,L10, NP
1100830	Lifelight Pro Head Assembly, Round
8001730	PCA:STU t/s Clever-test, #CT10080-A5

clevertest™

LP™ PREMIUM
LITHIUM BATTERY RANGE

Version: November 2016-I
www.clevertronics.com.au

 **Clevertronics®**
Emergency lighting innovation