



## CLEVERTRONICS LP LIFELIGHT PRO SURFACE MOUNT EMERGENCY (DLI)



### PRODUCT INFORMATION

Catalogue Number	CLIFE-2PRO-SMS-DLI-1200
Description	LP Premium LifeLight PRO, High Performance, Surface Mount Twin Emergency Light with Lithium Battery Technology
Construction	Powder Coated Metal Enclosure
Mounting	Surface Mount and can also be chain suspended
Dimensions L x W x H	1220mm x 110mm x 50mm
Operating Mode	Non-maintained
Testing System	DLI compatible
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x 3W LED (Lifetime warranty on the Lamp head and loom Assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.8 Watts (Standby), 4.4 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D125 C <sub>90</sub> =D125

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
LLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,L10, NP
1100830	Lifelight Pro Head Assembly, Round
8002200	PCA:DLI Node, #CT10410-A3

