



CLEVERTRONICS LP LIFELIGHT PRO SQUARE, BLACK



PRODUCT INFORMATION

| | |
|-----------------------|--|
| Catalogue Number | CLIFE-PRO-DALI-SQ-BLK |
| Description | LP Premium LifeLight PRO Square, High Performance, Recessed Emergency Light, Black |
| Construction | PC/ABS Head |
| Mounting | Recessed Mount |
| Dimensions L x W x H | 232mm x 40mm x 40mm (Control Pack) 60mm x 60mm (Head) |
| Ceiling Hole Cut-Out | 51mm, 85mm (with adaptor plate) |
| Minimum Ceiling Depth | 200mm, 120mm (with adaptor plate) |
| Weight | 1.5kg |
| Operating Mode | Non-maintained |
| Testing System | DALI compatible |
| Battery | Lithium Iron Phosphate, 3.2V 6400mAh |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Lamp(s) | 2 x 3W LED (Lifetime warranty on the Lamp head and loom Assembly) |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 0.4 Watts (Standby), 4.7 Watts (Max) |
| IP Rating | IP20 |
| Operating Temperature | 1°C to 40°C |
| AS2293 Classification | C ₀ =D63 C ₉₀ =D63 |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|----------------|--|
| 1550230 | BATT:LP 3.2V 6400mAh.200mm lead.Brkt. |
| CLIFE-PRO-CKIT | Lifelight Pro, Control Only, LP Lithium |
| 1100835 | Lifelight Pro Head Assembly, Round,Black |
| 8002200 | PCA:DALI Node, #CT10410-A3 |

