

CLEVERTRONICS LP LIFELIGHT PRO, BLACK



PRODUCT INFORMATION

Part Number	CLIFE-PRO-ZW-BLK
Description	LP Premium Lifelight PRO, high performance, recessed Emergency Light, Black
Construction	PC/ABS head
Mounting	Recessed mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 60mm head diameter (95mm with adaptor plate)
Ceiling Hole Cut-Out	51mm, 85mm (with adaptor plate)
Minimum Ceiling Depth	200mm, 120mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Zoneworks Computerised Testing
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4 Watts (Standby), 4.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D63 C ₉₀ =D63

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
CLIFE-PRO-CKIT	Lifelight Pro, Control Only, LP Lithium
1100834	Lifelight Pro Head Assbly,Rnd,LrgRingBlk
8001450	PCA:Powerline Node ZW, #CT10310-A6

