



## CLIFE-ZW CLEVERTRONICS LP LIFELIGHT



### PRODUCT INFORMATION

Part Number	CLIFE-ZW
MIC	AUD02110020001
Description	LP Premium Lifelight, High Performance, Recessed Emergency Light
Construction	ABS head and PC/ABS control gear
Mounting	Recessed mount
Dimensions L x W x H	232mm x 51mm x 42mm (Control Pack) 95mm Head Diameter (145mm with adaptor plate)
Ceiling Hole Cut-Out	85mm, 135mm (with adaptor plate)
Minimum Ceiling Depth	120mm, 70mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Zoneworks computerised testing
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Single white LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	1.3 Watts (Standby), 4.5 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D40 C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550010	BATT:LP 3.2V 3200mAh 200mm lead,BRKT.
1100925	LifeLight Head Assembly, Round, LT, 1LED
AUM02170120001 CLIFE-CKIT-ZW	Lifelight: LED, Recess Round, ZW, LP, OWC, Wht Led (incl. ZW node)
8001450	PCA:Powerline Node ZW, #CT10310-A6

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order