



## CLEVERTRONICS LP DALI PROFESSIONAL WEATHERPROOF BATTEN



Gen 1



Gen 2

### PRODUCT INFORMATION

Catalogue Number	CWB214S-P-DB-DALI
Description	2 x 14 Watt LP Premium Professional Weatherproof Batten with DALI ballast and LED Emergency Pod
Construction	Polycarbonate Base and Diffuser with Powdercoated Metal Gear Tray and Tamper proof Stainless Steel Clips
Mounting	Surface Mount
Dimensions L x W x H	720mm x 160mm x 105mm
Weight	2.8kg
Operating Mode	Sustained
Testing System	DALI compatible
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Ballast	DALI Dimmable, EEI=A1
Lamp(s)	T5 Cool White Tri-Phosphorous 14W/840
Operating Voltage	240V AC; 50Hz
Power Consumption	32 Watts (Lamps ON) 1.0 Watts (Lamps OFF)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	C <sub>0</sub> =D40 C <sub>90</sub> =D40
Impact Rating	IK08

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery, LP 3.2V 3200mAh 70mm lead, no Bracket
1320004	2x14/24w Dali Dimmable Ballast, A1
CLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,LP, NP
8002200	PCA:DALI Node, #CT10410-A3

DALI EM

**LP** LITHIUM IRON PHOSPHATE  
**PREMIUM**  
 PROVEN PROJECT PERFORMANCE