



CLEVERTRONICS LP WEATHERPROOF BATTEN



Gen 1



Gen 2

PRODUCT INFORMATION

Catalogue Number	CWB228S-P-CT
Description	2 x 28 Watt LP Premium Weatherproof Batten with LED Emergency POD
Construction	Polycarbonate Base and Diffuser with Powdercoated Metal Gear Tray and Tamper proof Stainless Steel Clips
Mounting	Surface Mount
Dimensions L x W x H	1330mm x 160mm x 110mm
Weight	4.0kg
Operating Mode	Sustained
Testing System	Clevertest
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Ballast	High Frequency Electronic Ballast EEI= A2
Lamp(s)	T5 Cool White Tri-Phosphorous 28W/840
Operating Voltage	240V AC; 50Hz
Power Consumption	62 Watts (Lamps ON) 1.0 Watts (Lamps OFF)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40
Impact Rating	IK08

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery, LP 3.2V 3200mAh 70mm lead, no Bracket
1310080	2x14-35w QT-FIT5 Elect Ballast , A2
CLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,LP, NP
8001730	PCA:STU t/s Clever-test, #CT10080-A5

