



CLEVERTRONICS LP WEATHERPROOF BATTEN



Gen 1



Gen 2

PRODUCT INFORMATION

| | |
|-----------------------|--|
| Catalogue Number | CWB228S-P-DALI |
| Description | 2 x 28 Watt LP Premium Weatherproof Batten with LED Emergency POD |
| Construction | Polycarbonate Base and Diffuser with Powdercoated Metal Gear Tray and Tamper proof Stainless Steel Clips |
| Mounting | Surface Mount |
| Dimensions L x W x H | 1330mm x 160mm x 110mm |
| Weight | 4.0kg |
| Operating Mode | Sustained |
| Testing System | DALI compatible |
| Battery | Lithium Iron Phosphate, 3.2V 3200mAh |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Diffuser | Polycarbonate |
| Ballast | High Frequency Electronic Ballast EEI= A2 |
| Lamp(s) | T5 Cool White Tri-Phosphorous 28W/840 |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 63 Watts (Lamps ON) 1.0 Watts (Lamps OFF) |
| IP Rating | IP65 |
| Operating Temperature | 0°C to 40°C |
| AS2293 Classification | C ₀ =D40 C ₉₀ =D40 |
| Impact Rating | IK08 |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------------|--|
| 1550050 | Battery, LP 3.2V 3200mAh 70mm lead, no Bracket |
| 1310080 | 2x14-35w QT-FIT5 Elect Ballast , A2 |
| CLIFE-PRO-CKIT-NP | LifelightPro,Control Only,Batten,LP, NP |
| 8002200 | PCA:DALI Node, #CT10410-A3 |

DALI EM

LP LITHIUM IRON PHOSPHATE
PREMIUM
 PROVEN PROJECT PERFORMANCE