

CLEVERTRONICS LP ARGONAUT PRO WIDE BODY MAINTAINED WEATHERPROOF BATTEN WITH INTEGRAL BATTERIES (DALI)



PRODUCT INFORMATION

Catalogue Number	CWB2LEDM-P-WB-IB-PRO-DALI
Description	LP Premium, 2ft Argonaut PRO LED Weatherproof Batten with Integral Batteries
Construction	Glass Fibre Reinforced (GRP) Base, Polycarbonate Diffuser with Powder coated Metal Gear Tray and Stainless Steel clips
Mounting	Surface Mount
Dimensions L x W x H	662mm x 158mm x 100mm
Operating Mode	Maintained
Testing System	DALI compatible
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
LED Driver	OSRAM OT FIT, 50,000hr
Lamp(s)	LED module, 4,000K Natural White, Ra>80, 44,000h Life [L80/B20 Ta 40°C], 50,000h Life [L70/B10 Ta 40°C]
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Total lumen output	1950 lm @ 111lm/W (118lm/W for non-Em version)
Power Consumption	17.5Watts (LED strip ON), 1.0 Watts (LED Strip OFF - standby)
IP Rating	IP66
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D80 C ₉₀ =D32
Impact Rating	IK07 (Base), IK09 (Diffuser)

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550260	BATT:LP 6.4V 3200mAh 200mm lead.SBS.
1330035	LED Driver - 35W, 500-700mA, 27-54V
8002675	PCA:60 LED Strip 600mm for Argonaut PRO
CCPLED-38V120C-CKIT	LED Power Pack, 38V 120mA, LP
8002205	PCA:DALI Node, Horizontal #CT10410-A3

DALI EM

LP LITHIUM IRON PHOSPHATE

PREMIUM

PROVEN PROJECT PERFORMANCE